



# TECHNICAL DATA Bulletin


Revision: 2018-08-03



## Platinum Patch™ Advanced Exterior Filler

Product Description: **DAP® PLATINUM PATCH™ Advanced Exterior Filler** with WeatherMax™ Technology is a waterproof, weatherproof and mould & mildew resistant formula making it ideal for exterior applications. It provides unsurpassed performance for filling holes & cracks in surfaces such as metal, composite, PVC, fibre cement, wood and more. It's easy to apply, sandable and paintable and low in odour.

### MADE FOR THE ELEMENTS



**Multi-Material Adhesion**



**Sandable & Paintable**



**24 Hour Rain Ready**

#### Featured & Benefits:

- WeatherMAX Technology
  - Weatherproof, Waterproof, Mould & Mildew Resistant
- For the most demanding repairs
- Ideal for exterior applications
- Multi-Material Adhesion
  - Metal, Composite, PVC, Wood Vinyl & More
- Sandable & Paintable

#### Suggested Uses:

Ideal for filling holes, cracks, crevices, dents or defects on:

- Aluminium/Steel
- Composite
- PVC
- Fiber Cement
- Wood
- Mortar
- Concrete
- Vinyl
- Brick
- Stucco
- Plaster
- Drywall

#### Available In:

| SKU #      | Description                             | Size                | Package Type | Case Pack | Color |
|------------|---|---------------------|--------------|-----------|-------|
| 7079874887 | Platinum Patch Advanced Exterior Filler | 7 Fl. Oz. (207 mL)  | Tube         | 6 PK      | White |
| 7079874888 | Platinum Patch Advanced Exterior Filler | 32 Fl. Oz. (946 mL) | Tub          | 8 PK      | White |



# TECHNICAL DATA SHEET

## Surface Preparation & Application Instructions:

- Surface must be clean, dry and free of foreign material.
- If using squeeze tube, knead tube before use and cut nozzle to desired opening size.
- Apply with a clean putty knife.
- For a smoother finish, dip putty knife in water and lightly smooth.
- One application is usually sufficient for small repairs. For repairs deeper than 3mm, apply two or more layers allowing to dry between applications.
- May be sanded and/or painted in 2 to 4 hours depending on temperature, humidity and depth of fill. Wet sanding is recommended to avoid generation of dust.
- Clean tools immediately with water.

## For Best Results:

- Do not apply when temperatures are below 5°C.
- Allow product to fully cure before exposing to water, approximately 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- A topcoat is not required, however, if desired, product can be painted with a high-quality latex-based paint.
- Staining is not recommended.
- Not for continuous underwater use.

## Typical Physical & Chemical Characteristics:

|                         |   |
|-------------------------|---|
| Consistency             | Paste   |
| Vehicle                 | Acrylic Latex   |
| Volatile                | Water   |
| Odour                   | Slight  |
| Specific gravity        | 1.6   |
| Solids                  | 79% by weight   |
| Application Temperature | 5°C - 65°C  |
| Service Temperature     | -17°C to 50°C   |
| Shelf Life              | 12 months   |
| Freezing                | Passes 5 cycles of 16 hours at -17°C / 8 hours at 22°C            |
| Dry Time                | 2 to 4 hours depending on temperature, humidity and depth of fill |
| SDS Number              | 00010500605   |



# TECHNICAL DATA SHEET

## Cleanup & Storage Recommendations:

- Wash tools immediately after use with water.
- Dried material must be removed by scraping or sanding.
- Be sure container lid/cap is closed and tightly sealed.
- Store in a cool, dry place.

## Safety & Warranty Information:

- See product label and Safety Data Sheet (SDS) for health and safety information.
- For an SDS, contact your supplier or visit [dap.com](http://dap.com).
- If product fails to perform as directed, within one year from the date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund.
- DAP will not be liable for incidental or consequential damages.

## Disclaimer:

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use.

## Company Information:

Manufactured for: DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON. M1X 1B7

Usage Information: Call 888-DAP-TIPS or visit [dap.com](http://dap.com) & click on "Ask the Expert"

Order Information: 800-327-3339

Fax Number: 410-558-1068

Also visit the DAP website at [dap.com](http://dap.com).