



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Ready-To-Use Concrete Patch

PRODUCT DESCRIPTION

DAP® Ready-To-Use Concrete Patch is a ready to use latex-based compound with fiber reinforcement to increase durability & for a long-lasting repair. Perfect for repairing holes, cracks, breaks & spalls in concrete or masonry surfaces. The product is excellent for tuck pointing masonry and brick work. It may also be used as a “glue” to join broken pieces of concrete or brick. DO NOT USE AS A SKIM COAT. The material dries to a concrete-grey color.



PACKAGING	COLOUR	SKU	UPC
946 mL	Grey	7079817100	0 7079817100 8
3.8L	Grey	7079817150	0 7079817150 3

KEY FEATURES & BENEFITS

- Repairs cracks and breaks in concrete and masonry
- Durable and shrink-resistant
- Can be used to spot level

SUGGESTED USES

Ideal for filling holes, cracks, dents and defects on concrete.

APPLICATION

1. Use a wire brush, chisel, or similar tool to remove all loose material, dust, dirt, oil and grease from the area to be repaired. Use a solvent to remove oil and grease. Rough up the surface 2.54cm or 5.04cm (1-inch or 2-inch) beyond the area to be repaired for a good bond. Dampen the area with clean water – DO NOT FLOOD.
2. Stir the patch to a smooth consistency; no thinning is required. With a flexible putty knife, broad knife, or trowel fill in the area to be repaired, pressing compound firmly into holes or cracks. Wet the putty knife with water to help achieve a smooth film.
3. If area to be patched is deeper than 1.27cm (1/2 inch), apply patch in 0.64cm (1/4-inch) layers, maximum depth 2.54cm (1 inch), allowing each application to dry.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

4. If used as a “glue,” apply at least one layer of concrete patch to both surfaces to be repaired. Push the pieces together and use bracing or weights to support the assembly during cure.
5. Patched areas may be painted with a quality latex paint after 3 to 5 hours or alkyd paint after 48 hours if desired.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Grey
Base Polymer	Latex Emulsion
Weight % Solids	79.6%
Density (lbs per gallon)	11.96
Odour	Mild
Clean Up	Water
Shelf Life	12 months in original, unopened container
Coverage	946mL covers approximately 2 sq. ft. at 1/8 in. 3.8L covers approximately 8 sq. ft. at 1/8 in.
Storage Conditions	Store between 4.4°C to 32°C (40°F and 90°F). Keep container tightly sealed when not in use.
Typical Application Properties	
Application Temperature	Temperature greater than 4.4°C
Set Time	3 – 5 hours at 0.64 cm (1/4" depth)
Full Cure	48hrs depending on the temperature and humidity for 0.64 cm (1/4") depth



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

CLEAN UP & STORAGE

Clean hands and tools with soap and water. Dry material must be cut or scraped away. Keep from freezing. Keep container tightly sealed when not in use. Store between 4.4°C to 32°C (40°F and 90°F).

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS by visiting our website at dap.ca or calling 888-DAP-TIPS.

WARRANTY

If product fails to perform when used as directed, call 888-DAP-TIPS for replacement product or sales price refund. DAP Canada will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufactured for: DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON, M1X 1B7

Usage Information: Call 888-DAP-TIPS or visit dap.ca & click on "Ask the Expert"

Order Information: 800-668-9397 or 416-321-1522

Fax Number: 416-321-3325

Also visit the DAP website at dap.ca