



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® Textured Concrete Premium Elastomeric Latex Filler & Sealant

### PRODUCT DESCRIPTION

DAP® Textured Concrete Premium Elastomeric Latex Filler & Sealant is used for repairing and sealing cracks and joints in concrete, masonry, stone, cinder block, and brick. The grey textured finish blends easily with concrete and provides excellent outdoor durability. Forms a durable, 100% waterproof and weatherproof seal. 2 Hour Paintability. Easy water clean up & won't stain or bleed onto the application surface. Interior/exterior use.



PACKAGING	COLOUR	SKU	UPC
300mL (10.1 fl oz) Cartridge	Textured Grey	7079874332	070798743328

### KEY FEATURES & BENEFITS

- Fills and seals cracks and holes in concrete surfaces
- Ready to use – needs no mixing or additives
- Provides a durable, long-lasting repair that is resistant to gasoline, salt, grease or oil when cured
- Cured sealant is mildew resistant
- 100% waterproof & weatherproof seal
- Excellent adhesion & flexibility for a durable seal
- Textured to blend with concrete & masonry surfaces
- Easy water clean up & low odour
- Won't stain or bleed
- 2 hour paint ready
- Safe for vehicle & foot traffic
- Exterior/Interior



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## SUGGESTED USES

### FILLING & SEALING CRACKS & GAPS IN:

- Concrete surfaces
- Concrete Patios
- Concrete Steps
- Above ground foundations
- Concrete driveways
- Concrete Sidewalks
- Concrete Garage floors

### ADHERES TO:

- Concrete
- Mortar
- Brick
- Stone
- Cinderblock
- Stucco
- Wood
- Most metals
- Other construction materials

## FOR BEST RESULTS

- Apply in temperatures above 4°C (40°F). Do not apply when rain or freezing temperatures are forecasted.
- Not for continuous underwater use.
- Joint size should not exceed 1.27 cm (1/2") wide by 1.27 cm (1/2") deep. If joint exceeds depth of 1.27 cm (1/2"), use foam backer rod. Allow to dry 24 hours before direct exposure to water.
- Serviceable for pedestrian & vehicular traffic after 24 hours (minimum).
- Fully dries in 2-4 days, depending on temperature, humidity & depth of fill.
- Store sealant away from extreme heat or cold.

## APPLICATION

### Surface Preparation

Surface must be clean, dry, structurally sound and free of all foreign material.

### Product Application

1. Apply in temperatures above 4°C (40°F). Do not apply when rain or freezing temperatures are forecasted within 24 hours. Cooler temperatures and higher humidity will slow down dry time.
2. Cut nozzle at 45° angle to desired bead size.
3. Load cartridge into caulk gun.
4. Fill cracks and gaps with sealant.
5. After, a more uniform fill or neater appearance application may be obtained by tooling lightly with a trowel or putty knife.
6. Allow to fully dry 24 hours before direct exposure to water (longer in cooler and/or humid conditions).
7. Paintable after 2 hours (longer in cool or humid conditions) with latex or oil-based paints.
8. Clean up excess wet sealant with a damp sponge before it skins over (30 minutes). Excess dried sealant must be cut or scraped away. Reseal cartridge for future use. Store away from extreme heat or cold.
- 9.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

<b>Typical Uncured Physical Properties</b>	
Appearance/Consistency	Smooth and creamy
Base Polymer:	Acrylic Latex
Filler:	Calcium carbonate
Volatile:	Water
Weight % Solids	73 % by weight
Density (lbs per gallon )	11.7 lbs/gal
Odour	Very mild
Clean Up	Water
Flash Point	100°C
Freeze Thaw Stability:	Passes 5 Cycles
Shelf Life	12 months
Coverage	16.76 m (55 linear feet) at 0.48cm (3/16") diameter bead
<b>Typical Application Properties</b>	
Application Temperature Range:	4°C to 37°C
Tooling Time (Working Time)	10 minutes
Tack Free Time	30 minutes
Full Cure Time	2 – 4 days
Return to Service Time	24 hrs
Vertical Sag (D2202)	0.127
<b>Typical Cured Performance Properties</b>	
Service Temperature Range:	-28°C to 82°C
Water Ready Time	24 hours
Paint Ready Time	2 Hours



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## CLEAN UP & STORAGE

Clean up excess uncured caulk with a damp sponge before it skins over (approximately 30 minutes). Excess dried caulk must be cut or scraped away. Clean hands and tools with warm, soapy water. Store in a cool, dry place away from extreme heat or cold.

## SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS by visiting our website at [dap.com](http://dap.com) or calling 888-DAP-TIPS.

## WARRANTY

**LIMITED WARRANTY:** If product fails to perform when used as directed, call 888-DAP-TIPS for replacement product or sales price refund. DAP Canada will not be responsible for incidental or consequential damages.

## COMPANY IDENTIFICATION

**Manufactured for:** DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON, M1X 1B7

**Usage Information:** Call 888-DAP-TIPS or visit [dap.ca](http://dap.ca) & click on "Ask the Expert"

**Order Information:** 800-668-9397 or 416-321-1522

**Fax Number:** 416-321-3325

**Also visit the DAP website at [dap.ca](http://dap.ca)**