



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 06/18/2019

DAP® EXTREME STRETCH™ Premium Crackproof Elastomeric Sealant

Premium Quality, Urethanized All-Purpose Caulk

- Stretches up to 600%
- Adheres to virtually any substrate
- Paintable in 2 hours
- 100% Crackproof
- Seals joints up to 3” wide
- Easy water clean-up
- Low odor
- Interior/Exterior

Packaging: 10.1 fl. oz. (300 mL) cartridge
Color: White
UPC Number: 7079874865

Company Identification:

Manufactured for: DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON. M1X 1B7
Usage Information: Call 1-888-DAP-TIPS or visit dap.ca & click on “Ask the Expert”
Order Information: 800-668-9397 or 416-321-1522
Fax Number: 416-321-3325
Also, visit the DAP website at dap.ca

Product Description:

DAP® EXTREME STRETCH™ is a premium urethanized caulk ideal for sealing a wide variety of interior & exterior surfaces. EXTREME STRETCH stretches up to 600% and provides superior adhesion for a long lasting durable seal. Its unique formula is easy to apply & tool, low in odor & cleans up easily with water. Perfect for most sealing projects including windows, doors, trim, siding, gutters, flashing, sinks, and countertops.

Ideal for Caulking and Sealing:

- Windows
- Doors
- Siding
- Eaves
- Vents
- Baseboards
- Crown Molding
- Soffits
- Countertops
- Sinks

Adheres to:

- *Wood*
- *Fiber Cement*
- *Tile*
- *Metal*
- *Plexiglass*
- *Fiberglass*
- *Stucco/Brick*
- *Vinyl*
- *Drywall*
- *Glass*
- *Aluminum*
- *Asphalt*
- *PVC Trimboard*
- *Mortar/Stone/Cinder Block*
- *Concrete*
- *EIFS*
- *Most Plastics*

Performance Characteristics:

- Ready to use – needs no mixing or additives.
- Offers excellent weatherability to resist UV light and temperature extremes without cracking, bubbling or becoming brittle.
- Provides a durable, long-lasting seal.
- Cured caulk is mildew resistant.
- Water clean-up.

Performance Characteristics:

- Exceeds the requirements of ASTM C920 standard specification for Elastomeric joint sealants, Type S, Grade NS, Class 25. Use NT, G, A and M.
- Meets the performance specifications of Federal Spec TT-S-00230c (COMNBS0), Type II, Class A
- Exceeds ASTM Spec C834 Standard Specification for Latex Sealants

Surface Preparation & Application:

1. **Surface must be clean, dry and free of all old caulk, dirt, dust and grease.**
2. Cut nozzle at a 45° angle to desired bead size.
3. Load into caulk gun.
4. Fill gap with sealant, pushing sealant ahead of nozzle.
5. For professional results, smooth bead of sealant with a finishing tool.
6. Clean up excess uncured sealant with a damp cloth before it skins over (15 minutes). Cured sealant must be cut or scraped away.
7. Allow sealant to dry 2-4 hours before painting with latex paints. Cool or humid conditions or type of paint used may require longer dry time.
8. Reseal cartridge for storage and reuse.

For Best Results:

- Apply in temperatures above 40°F.
- Do not apply if rain or freezing temperatures are forecasted before full cure can occur. Cold weather and high humidity will slow down cure time.
- Do not use below waterline or for marine or automobile applications, or filling surface defects.
- Joint size should not exceed 3” wide by 1/2” deep. If joint depth exceeds 1/2”, use foam backer rod.
- Store sealant away from extreme heat or cold.

Typical Physical & Chemical Characteristics:

Vehicle: Acrylic Emulsion
Volatile: Water

Pigment:	Limestone
Solids:	74% by weight
Density	10.9 lbs. / gal.
Application Temperature:	40°F to 100°F
Service Temperature:	-30°F to 180° F
Freeze/Thaw Stability:	Passes 5 cycles of 16 hours at -18°C and 8 hours at 23°C
Consistency:	Smooth
Applications:	Interior/Exterior
Shelf Life:	1-year minimum
Coverage:	55 linear feet at 3/16" diameter bead
SDS No:	00040003001

Clean Up:

Clean excess caulk with a damp cloth before it skins over. Dried material must be cut or scraped away.

Safety:

See product label or Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.ca.

Lifetime Guarantee:

DAP warrants this product for sealant purposes during the lifetime of your home when applied within one year of purchase and as directed. If product fails to perform when used as directed, return container and sales receipt to DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON. M1X 1B7 for replacement product or sales price refund. DAP will not be liable for incidental or consequential damages.